



EU Declaration of Conformity

We authorised representative

CARLO GAVAZZI LTD...

BLB042, Bulebel Industrial Estate, Zejtun, ZTN3000, MALTA. Tel: +356 23601101 - Fax: +356 23601111

declare that the product(s)

RM / RAM Solid State Relay Series' : RM1A, RM1B, RAM1A_G, RAM1B_G, RAM1A_M, RAM1A_MP

is(are) in conformity with the applicable essential requirements of the following Directives:

Low Voltage Directive 2014/35/EU

Low-voltage switchgear and control gear. Part 4-2: Contactors and motor starters EN 60947-4-2: 2012

- AC semiconductor controllers and contactors for motor loads (*)

EN 60947-4-3: 2014 Low-voltage switchgear and control gear. Part 4-3: Contactors and motor starters

- AC semiconductor controllers and contactors for non-motor loads

EMC Directive 2014/30/EU

EN 60947-4-3: 2014 Low-voltage switchgear and control gear. Part 4-3: Contactors and motor starters

- AC semiconductor controllers and contactors for non-motor loads

RoHS Directive 2011/65/EU and 2015/863/EU amendment

EN 50581: 2012 Technical documentation for the assessment of electrical and electronic products

with respect to the restriction of hazardous substances

CE

CE marking: Design and manufacturing follow the provisions within the above-mentioned European Directives.

for the Authorised representative

Place/date

Malta, 1st April, 2020

Signature Name

Darren Harrison

moren Harrisen

(Director of Switches Division)

Notes:

This Manufacturer's Declaration of Conformity is only valid under the condition that:

The above-mentioned products are installed as prescribed in the installation documentation, protected against accidental touch and fitted to a heatsink which is connected to ground.

The above-inelitorite products are installed as prescribed in the installation documentation, protected against accidental touch and fitted to a heatsink which is connected to ground that the RoHS requirements is subject to supplier declarations and/or signed contractual agreements.

It shall be the responsibility of the system integrator to ensure that the system containing the above component complies with the applicable rules and regulations for their system. The control terminals shall be supplied by a power limited (short-circuit rating limit <1500VA) secondary circuit, if not then additional suppression maybe required. It is recommended that the control lines to this component are installed together (ie. two core cable) to ensure the RFI susceptibility level is maintained.



